

Printashrink Non-slip

Printashrink Non Slip is a heatshrinkable sleeve with a textured, non-slip surface. It is ideal for grips and handles. It is flexible, has good abrasion resistance and is available in several colours and sizes up to 50mm and can be [cut](#) as required.

This specially formulated polymer with a non-slip surface is available in mono or dual colours. It can be supplied in a variety of colours and with or without diamond patterning. It has a low shrink temperature which makes it perfect for the repair or manufacture of tools and machinery, fishing rods, sports and health equipment and safety handles.



Technical Data

- **Shrink Ratio:** 2:1
- **Shrink Temperature** 70°C
- **Operating Temperature** -55°C – +105°C
- **Colours:** Black, Blue, Red, Yellow, Green, Black/Red, Yellow/Red
- **Sizes:** 20mm ? 50mm
- **Packing:** 1.6 metre lengths, cut to length, cut sleeves
- **Approvals:** RoHS compliant
- **Applications / Industries:** General, Commercial, Industrial

Properties	Typical Values	Test Methods
General		
Operating Temperature	-55°C – +105°C	
Minimum shrink temperature	70°C	
Full recovery temperature	105°C	
Shrink Ratio	2:1	
Physical		
Tensile Strength	10.4Mpa	
Electrical		
Dielectric strength	10kV/mm	

Size (mm)	Supplied diameter (mm)	Shrunk diameter (mm)	Nominal wall thickness (mm)
20	20	11.0	0.90
25	25	14.5	1.00
30	30	17.5	1.20
35	35	21.0	1.20
40	40	23.0	1.20
50	50	28.0	1.25

Printasleeve Ltd is as diligent as possible in compiling and updating the above information. It reflects averages derived from product sample testing, is subject to normal manufacturing and testing tolerances and may be changed without notice. Furthermore aesthetic and textural style differences can result in local variation. For specific or further information concerning our products, their specifications and their utilisation please contact us. E & OE