



PVC GP

PVC GP is a general purpose, flexible non-shrink sleeve with an operating temperature of -25°C-+70°C. It is a low cost solution ideal for many commercial applications and is available in a full range of colours and sizes as standard and can be cut and printed as required.

This general purpose PVC hose is a low cost flexible jacket with good dielectric properties, chemical and fungal resistance and low water absorption. It is manufactured from premium virgin grade compound and frequently used in wire harnessing for electrical insulation. It is also used for general protection in a great many other applications including scooter/Vespa/motorcycle maintenance and retro/ period lighting. It is supplied with a 0.5mm nominal wall and in a wide range of metric and AWG sizes and colours including green/yellow for earth as standard. Bespoke sizes and colours are available on enquiry.

| Properties | Typical Values |
|-----------------------|---------------------------|
| GENERAL | |
| Operating temperature | 25°C – + 70°C |
| PHYSICAL | |
| Tensile strength | 15MPa |
| THERMAL | |
| Flammability | Self extinguishing in 30s |
| ELECTRIAL | |
| Dielectric strength | 20kV/mm |
| Insulation Resistance | 10 ¹¹ Ohm/cm |

TECHNICAL DATA

- **OPERATING TEMPERATURE**
-25°C-+70°C
- **FLAME RETARDANT**
Self extinguishing
- **COLOURS**
Black, Brown, Blue, Green, Yellow, Grey, White, Red, Green / Yellow, (Pink / Violet / Orange available to order)
- **SIZES**
1mm – 25mm
- **PACKING**
Coils, reels, cut to length, cut sleeves
- **PRINT**
Yes, full range of text and logos
- **APPROVALS**
RoHS Compliant
- **APPLICATIONS / INDUSTRIES**
General, Commercial, Electrical, Electronics, Industrial, Mechanical, Automotive

| Size (mm) | Supplied diameter (mm) | Nominal wall thickness (mm) |
|-----------|------------------------|-----------------------------|
| 1 | 1.0 | 0.40 |
| 1.5 | 1.5 | 0.40 |
| 2 | 2.0 | 0.40 |
| 3 | 3.0 | 0.40 |
| 4 | 4.0 | 0.40 |
| 5 | 5.0 | 0.45 |
| 6 | 6.0 | 0.45 |
| 8 | 8.0 | 0.45 |
| 10 | 10 | 0.45 |
| 12 | 12.0 | 0.45 |
| 15 | 15.0 | 0.45 |
| 18 | 18.0 | 0.45 |
| 20 | 20.0 | 0.45 |
| 25 | 25.0 | 0.45 |

Printasleeve Ltd is as diligent as possible in compiling and updating the above information. It reflects averages derived from product sample testing, is subject to normal manufacturing and testing tolerances and may be changed without notice. Furthermore aesthetic and textural style differences can result in local variation. For specific or further information concerning our products, their specifications and their utilisation please contact us.