



PTFE TW

PTFE TW (Polytetrafluoroethylene) is a non-flammable, thin-wall sleeving with an exceptionally high operating temperature of -70°C+260°C. It has a very low coefficient of friction, high dielectric strength and is virtually inert to all chemicals. It is available in many colours and AWG, metric and imperial sizes as standard. Bespoke sizes, wall thicknesses and colours are also available.

PTFE hose and convoluted tubing is ideal for enhanced protection of wire, cable, electrical and electronic components for commercial and high performance military and aerospace systems. It is extremely stable at very high temperatures and retains a measure of toughness and strength even at cryogenic temperatures. It is virtually inert to all chemicals resisting most acids. Alkalies and petroleum products. It is virtually unaffected by oxygen, ozone and UV light. It is extremely hydrophobic and has a UL 94 rating of V-O. It also has a very low coefficient of friction and high dielectric strength and excellent mechanical properties.

Properties	Typical Values	
GENERAL		
Operating temperature	-70°C – +260°C	Din/VDE 0207, BS6724, RoHS compliant
Shelf Life	No special requirements	
PHYSICAL		
Tensile strength	Longitudinal -33N/mm ² , transverse 31N/ mm ²	
Ultimate elongation	Longitudinal -350%, transverse 610%	
Water absorption	0.01% max.	
Density	2.15g/cm ³	
Hardness	D 55	
Co-efficient of friction	Extremely low	
UV Resistance	Virtually unaffected by oxygen, ozone, visible or UV light	
THERMAL		
Flammability	Non-flammable	UL 94 VO
Gel Transition Range	320°C – 340°C	DTA
Limited Oxygen Index	0.25-0.50W/m.K	DIN 52612
ELECTRICAL		
Chemical resistance	Virtually inert to all chemicals, organic	
Dielectric strength	30kV/mm (safe figure 40kV/mm)	ASTM D149

TECHNICAL DATA

- **OPERATING TEMPERATURE**
-70°C-+260°C
- **FLAME RETARDANT**
Non-flammable
- **COLOURS**
Natural, Brown, Pink, Black, Yellow, Blue, Grey, Orange, Violet, Red, Green, White
- **SIZES**
TW30mm – TW0mm
- **PACKING**
Coils, reels, cut to length, cut sleeves
- **APPROVALS**
RoHS compliant
- **APPLICATIONS / INDUSTRIES**
General, Commercial, Electrical, Electronics, Industrial, Mechanical, Automotive, Military-defence, Aerospace

Size (mm)	Supplied diameter (mm)	Nominal wall thickness (mm)
TW30	0.33	0.23
TW28	0.41	0.23
TW26	0.51	0.23
TW24	0.58	0.25
TW22	0.71	0.25
TW20	0.91	0.3
TW19	1.02	0.3
TW18	1.14	0.3
TW17	1.27	0.3
TW16	1.42	0.3
TW15	1.57	0.3
TW14	1.73	0.3
TW13	1.93	0.3
TW12	2.16	0.3
TW11	2.44	0.3
TW10	2.72	0.38
TW9	3.02	0.38
TW8	3.43	0.38
TW7	3.84	0.38
TW6	4.29	0.38
TW5	4.83	0.38
TW4	5.44	0.38
TW3	6.07	0.38
TW2	6.81	0.38
TW1	7.62	0.38
TW0	8.53	0.38

Printasleeve Ltd is as diligent as possible in compiling and updating the above information. It reflects averages derived from product sample testing, is subject to normal manufacturing and testing tolerances and may be changed without notice. Furthermore aesthetic and textural style differences can result in local variation. For specific or further information concerning our products, their specifications and their utilization please contact us.