



SR

SR silicone rubber sleeving is a highly elastic, flexible, high and low temperature resistant tubing with excellent ageing characteristics. Bore sizes 0.5mm to 25mm with a 0.5mm wall thickness and a wide variety of colours including neon and metallic are standard. Bespoke diameters, wall thicknesses, colours and different curings also available as are cutting and printing services.

Silicone rubber hose is available with bores of 0.2mm up to 200mm. It is extremely useful for cable harnessing because of its high elasticity and flexibility. Micro bore sizes are commonly used on electrical applications, midrange sizes for liquids and powders in the food processing and pharmaceutical sectors, and the largest sizes for dielectric tubing and hot air ducting. Silicone rubber is valued for its strength, hygienic properties, longevity of life, flexibility and translucency (where applicable). We can supply Water Council and Food and Drug Administration (FDA) approved materials for use specifically within hygiene-critical applications. We also offer methanol resistant and anti-bacterial grades, platinum (non-yellowing) and peroxide curing and varying hardnesses.

TECHNICAL DATA

• OPERATING TEMPERATURE

- 40°C+200°C

• COLOURS

Full range of colours incl metallics and neon

• SIZES

1.5mm – 25mm

• PACKING

Coils, reels, cut to length, cut sleeves

• PRINT

Yes, text and logos subject to testing

• APPROVALS

FDA, BDR approved, RoHS compliant

• APPLICATIONS / INDUSTRIES

General, Commercial, Electrical, Electronics,

Properties	Typical Values
GENERAL	
Operating temperature	-40°C+200°C
PHYSICAL	
Tensile strength	10.3N/mm ²
Ultimate elongation	600%
Specific gravity	1.15 g/cm ³
Hardness	Shore A 60 (others hardnesses available)
UV Resistance	Excellent resistance to UV and ozone
Tear Resistance	25/mm ²
Impact Resistance	60%
Compression Set	20%
ELECTRICAL	
Dielectric strength	20kV/mm
CHEMICAL	
Fungus resistance	Excellent

Size (mm)	Supplied diameter (mm)	Nominal wall thickness (mm)
0.5	0.5	0.5 (many others also available)
0.75	0.75	0.5 (many others also available)
1	1	0.5 (many others also available)
1.5	1.5	0.5 (many others also available)
2	2	0.5 (many others also available)
2.5	2.5	0.5 (many others also available)
3	3	0.5 (many others also available)
3.5	3.5	0.5 (many others also available)
4	4	0.5 (many others also available)
4.5	4.5	0.5 (many others also available)
5	5	0.5 (many others also available)
6	6	0.5 (many others also available)
8	8	0.5 (many others also available)
10	10	0.5 (many others also available)
12	12	TBA
15	15	TBA
18	18	TBA
20	20	TBA
25	25	TBA

Printasleeve Ltd is as diligent as possible in compiling and updating the above information. It reflects averages derived from product sample testing, is subject to normal manufacturing and testing tolerances and may be changed without notice. Furthermore aesthetic and textural style differences can result in local variation. For specific or further information concerning our products, their specifications and their utilisation please contact us.

